



Amendment to Test Report	
This Amendment is valid only together with the main Test Report	
Report No	: 277780
Main Report No	: 246038
Date of issue	: January 26, 2015
Total number of pages	: 5
Applicant's Name	: Power Integrations, Inc.
Address	: 5245 Hellyer Avenue, San Jose, CA 95138, U.S.A.
Test specification	
Standard	: IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013 with CTL Decision, DSH 1080
Test procedure	: CB scheme
Non-standard test method	: N/A
<p>Copyright © 2010 Worldwide System for Conformity Testing and Certification of Electrotechnical Equipment and Components (IECEE), Geneva, Switzerland. All rights reserved.</p> <p>This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.</p> <p>If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.</p> <p>This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.</p>	
Test item description	: IC including capacitor discharge function (ICX)
Trade Mark	: CAPZero
Manufacturer	: Power Integrations, Inc.
Model/Type reference	: CAP002DG; CAP003DG; CAP004DG; CAP005DG; CAP006DG; CAP007DG; CAP008DG; CAP009DG; CAP012DG; CAP013DG; CAP014DG; CAP015DG; CAP016DG; CAP017DG; CAP018DG; CAP019DG; SC1143; CAP200DG
Ratings	: 230V AC nominal (tested for 85-265V AC, 47-63Hz)

Testing procedure and testing location:		
<input checked="" type="checkbox"/>	CB Testing Laboratory:	Nemko A/S
Testing location/ address :		Gaustadalléen 30, NO - 0373 Oslo, Norway
<input type="checkbox"/>	Associated CB Laboratory:	
Testing location/ address :		
Tested by (name + signature) :		Ole Morten Aaslund <i>Ole Morten Aaslund</i>
Approved by (name + signature) .. :		Hans-Eirik Lie <i>Hans-Eirik Lie</i>
<input type="checkbox"/>	Testing procedure: TMP	
Testing location/ address :		
Tested by (name + signature) :		
Approved by (name + signature) .. :		
<input type="checkbox"/>	Testing procedure: WMT	
Testing location/ address :		
Tested by (name + signature) :		
Witnessed by (name + signature) .. :		
Approved by (name + signature) .. :		
<input type="checkbox"/>	Testing procedure: SMT	
Testing location/ address :		
Tested by (name + signature) :		
Approved by (name + signature) .. :		
Supervised by (name + signature) :		
<input type="checkbox"/>	Testing procedure: RMT	
Testing location/ address :		
Tested by (name + signature) :		
Approved by (name + signature) .. :		
Supervised by (name + signature) :		

List of Attachments (including a total number of pages in each attachment):
N/A

Summary of testing:
N/A

Tests performed (name of test and test clause):	Testing location:

Summary of compliance with National Differences
N/A

Copy of marking plate
The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

Refer main report.

Calibration	All instruments used in the tests given in this test report are calibrated and traceable to national or international standards. Further information about traceability will be given on request.
Measurement uncertainty	Measurement uncertainties are calculated for all instruments and instrument set-ups given in this report. Calculations are based on the principles given in the standard EA-4/02 (Dec. 1999), IEC Guide 115:2007 and other relevant internal Nemko-procedures. Further information about measurement uncertainties will be given on request.
Evaluation of results	If not explicitly stated otherwise in the standard, the test is passed if the measured value is equal to or below (above) the limit line, regardless of the measurement uncertainty. If the measured value is above (below) the limit line, the test is not passed - ref IEC Guide 115:2007. The instrumentation accuracy is within limits agreed by IECEE-CTL.

Possible test case verdicts:

- test case does not apply to the test object : Not Applicable (N/A)
- test object does meet the requirement..... : Pass (P)
- test object does not meet the requirement : Fail (F)

Testing**Date of receipt of test item** : September 17, 2014**Date(s) of performance of tests** : September 17 – September 23, 2014**General remarks:**

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

"(see Enclosure #)" refers to additional information appended to the report.

"(see appended table)" refers to a table appended to the report.

Throughout this report a comma / point is used as the decimal separator.

Manufacturer's Declaration per sub-clause 6.2.5 of IECEE 02:

The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided..... : Yes Not applicable

When differences exist; they shall be identified in the General product information section.

Name and address of factory (ies) : Millenium Microtech Shanghai
No. 351 Guo Shou Jing Rd., Z.J. Hi Tech Park
Pudong New Area, Shanghai,
201203 CHINA

<p>General product information:</p> <p>The update concerned in this amendment report covers the introduction of new variant, model CAP200DG. This new variant is identical to model SC1143 except for model name.</p>
--

Project history:		
Nemko Report/ Order No.:	Modification to the appliances:	Changes/ Modifications in clause(s):
246038	Main Test Report	N/A
247613	Adding of voltage and frequency range; 85-265V AC, 47-63Hz. Note that DSH 1080 only covers Installation Category II (2.5kV transients), and end products using the ICX covered by this report must follow the same Installation Category.	Summary of testing, Test items particulars, General product information, 2.1.1.7
270272	Introduction of different minimum and maximum X-capacitance and resistance values: X-capacitance: Min. 100nF, max. 6µF Resistance: Min. 142kΩ, max. 7.5MΩ Refer also General product information. Upgrade to include Amd 2:2013 of IEC 60950-1(ed2).	Summary of testing, General product information, 2.1.1.7
277780	Addition of a new model CAP200DG. The new model is identical to model SC1143 except for model name. No additional testing required.	1.7.1.2

1.7.1.2	Identification markings	Refer below:	P
	Manufacturer's name or trade-mark or identification mark	CAPZero	P
	Model identification or type reference	CAP002DG; CAP003DG; CAP004DG; CAP005DG; CAP006DG; CAP007DG; CAP008DG; CAP009DG; CAP012DG; CAP013DG; CAP014DG; CAP015DG; CAP016DG; CAP017DG; CAP018DG; CAP019DG; SC1143; CAP200DG	P